



Good ideas and best solutions

IDZOR PR-200BW

Portable thermal printer



- Mini size, double injection molding and rubber protection around, durable enough for anti-dropping
- Non-slip design (salient points on the rubber of the two sides)
- Exclusive power indication light
- Support USB, power adapter or mobile power charging
- Has standby mode to save power
- Provide SDK for MS and Android



Good ideas and best solutions

Item Name:	2" Thermal Portable Printer PR-200BW
Printing way:	Thermal sensitive line dot method
Paper width:	58mm
Valid printing width:	48 mm
Paper thickness:	60 ~ 80µm
Rolling paper Diameter:	∅ 40(max)X58mm
Paper feeding method:	Easy paper loading
Resolution:	8 dot/mm (203 dpi)
Dot /line:	384 dots/line
Printing speed:	80 mm/s (max)
Print Font	ASCII Font A: 12×24/ASCII Font B: 9×24/Chinese: 24×24
Characters per Line	Font A: 32/Font B: 42/Chinese: 16
MCBF:	5 Million Lines
Print head lifespan:	50 km
Interface:	Bluetooth(BT4.0&BLE)/WiFi/USB/RS232
Barcode type:	CODE39/EAN-13/EAN-8/CODABAR/CODE93/ITF/QR/PDF417
Paper sensor:	Support
Printing Command:	ESC/POS
Battery:	1600 mAh rechargeable li-ion battery Continuously working for 5.5 hours or 195m 3.5 hours' charging time lifespan is more than 500 times.
Power alarm:	Exclusive power indication light turn off and red light flashes when the printer is running out of power. Then it must be charged or changed the battery.
Power Supply:	USB/Power adapter/mobile power charging
Environment parameters:	Working temperature: -10 °C ~ 50 °C Working humidity: 20% ~ 85% Storing temperature : -20 °C ~ 70 °C Storing humidity: 5% ~ 95%
Outer dimension(LxWxH):	112*79*45mm
Weight:	208g (including the paper roll and battery)
Packing dimension(LxWxH):	210x135x80mm